

MAP - CURE

Water based concrete curing compound

LIMITATIONS

- Concrete staining may occur if MAP CURE is applied to dry surfaces.
- MAP CURE should be protected from rain and traffic for three (3) hours aer application or until the membrane has completely dried.
- To prevent clogging, regular cleaning of jet sprays during application is recommended.
- It should not be over coated with other coating sor treatments. If material is to be applied over the top of a surface treated with MAP - CURE, sand blasting or solvent treatment is recommended as surface preparation.
- Early application of MAP CURE will help prevent plastic shrinkage cracks from occuring by reducing the amount of water evaporating.Concrete curing compound, however, will not counter the effects of

cracking that may occur as a result of long term drying & shrinkage. Good concrete practic emuss apply when positioning onsstructiont joints and shrinkage control joint.

PACKING & COVERAGE

Packing : 1, 5, 10, 50, 100 & 200 ltr. packaging. Coverage : 5-6 m²per liter

QUALITY ASSURANCE

MAP PRODUCTS PVT LTD. is a firm of Assessed Capability. The company conform to the standard quality system, environmental management and is an ISO 9001:2015, ISO 14001:2015 & OHSAS 18001:2007 Certified Company.

The information herein is based upon the best informaation available at the time of printing .Data provided is intended for those having skill and ability to use products recommended in a safe and responsible manner. LIABILITY is limited to the cost of material proven to be defective. There is no warranty expressed or implied as related to any issue which is deemed to be a direct result of improper acts of others or acts of GOD, constant submersion in harsh environments, workmanship or applicator, or any other cause and effect which is not related to deffective material.

