

MAP - BOND COAT

Bonding Key-coat for smooth surfaces

DESCRIPTION

MAP - BOND COAT, is a bonding agent, used to bond, stone, plaster and any type of smooth low suction surface and eliminate hacking (making surface rough, by making impression on to the smooth concrete surface) E.g. Concrete surfaces.

AREA OF APPLICATION

MAP - Bond Coat is used as a rush-coat / key-coat to provide a strong mechanical key on smooth concrete surfaces. It is suitable for use on walls, ceilings & stones. It is suitable for interior and exterior use. MAP - Bond Coat is designed for use with sand - cement render , gypsum plaster, machine plasters and spray plaster. It is suitable for use on smooth stone surface.

APPLICATION METHODOLOGY

MAP - Bond Coat is applied by brush or roller at a rate of approx 1 kg/m² to provide a textured mechanical key. Stir the contents of MAP - Bond Coat thoroughly, before use and apply evenly as a single coat. Allow it to dry thoroughly for around 24 hours. Clean tools and equipment with water after use.

ADVANTAGES

1. No Hacking. No structural & Masonry damage.
2. Provides chemical bonding properties as well as mechanical bonding to the surface it coated with
3. Easy to Apply.
4. No wastage of material.

MAP - BOND COAT

Bonding Key-coat for smooth surfaces

SHELF LIFE & STORAGE

MAP - Bond Coat has a shelf life of 12 months from date of manufacture when kept at a temperature between 5° C - 45° C and stored in the original unopened container.

COVERAGE

1 Kg/m2/Coat

PACKAGING

1, 5, 20 & 100 Kg

QUALITY ASSURANCE

MAP PRODUCTS PVT LTD. is a firm of Assessed Capability. The company conform to the standard quality system, environmental management and is an ISO 9001:2015 , ISO 14001:2015 & OHSAS 18001:2007 Certified Company.

HEALTH & SAFETY

MAP - Bond Coat should not come into contact with skin, eyes or be swallowed. Protective glasses should be worn during mixing and application. If MAP - Bond Coat comes into contact with skin, remove before hardening by washing with soap and water. If accidental eye contact occur wash with plenty of water and seek medical advice. If swallowed seek medical advice immediately. Do not induce vomiting. For full health and safety data refer to Product Safety Data Sheet.



CONCRETE
ADMIXTURE



WATERPROOFING
SYSTEM



MASONRY REPAIR




READYMIX
MORTAR



ENGINEERING
GROUT



FLOORING
SYSTEM



TECHNICAL TEXTILE
GLASS REINFORCEMENT



SEALANT



PROTECTIVE
COATING



ADHESIVE
BONDING AGENT

MAP PRODUCTS PRIVATE LIMITED

101-Labh, Shukan Tower, Above A.D.C. Bank, Judges Bunglow, Bodakdev, Ahmedabad, Guj. 380 054



+91 75748 09626



info@mapaac.in



www.mapaac.in



www.mapaac.in