

## colour shade

**MAP**<sup>TM</sup>  
Let's Build GREEN  
AN ISO 9001:2015 CERTIFIED COMPANY

**MAP**<sup>TM</sup>  
Let's Build GREEN  
AN ISO 9001:2015 CERTIFIED COMPANY

**MAP**  
Tile Grout & Epoxy TG  
**Colour Shade**

Authorised Dealer / Distributor :



**MAP**<sup>TM</sup>  
Let's Build GREEN  
AN ISO 9001:2015 CERTIFIED COMPANY

**MAP Products Pvt. Ltd.**  
101-Labh, Shukan Tower,  
Above A.D.C. Bank, Judges Bungalow,  
Bodakdev, Ahmedabad, Guj. 380 054  
Website : [www.mapaac.in](http://www.mapaac.in)  
Email : [info@mapaac.in](mailto:info@mapaac.in)  
M. : +91 75748 09626



## MAP - TILE GROUT

## COLOUR SHADES

## MAP - EPOXY TG



**MAP - TILE GROUT** is designed for joint width 1 mm to 3 mm for porous & absorbent type tiles, non-vitreous clay tiles, marble & glazed wall tiles.

**MAP - TILE GROUT** is a superior quality cementitious grout with hydrophobic properties that allow tile grouts to resist water. Used for filling joints 1 mm to 3 mm in both interior and exterior

**Coverage :** Approximate sq.ft. coverage per 1 kg pack of TILE GROUT. As per the Table below :

TILE SIZE X THICKNESS in mm	JOINT WIDTH		
	1 mm	2 mm	3 mm
100 x 100 x 3	143	72	48
150 x 150 x 4	161	81	54
200 x 150 x 5	147	74	49
150 x 300 x 6	143	86	47
300 x 300 x 6	215	72	71
450 x 300 x 7	220	110	74
600 x 450 x 8	275	138	92
600 x 600 x 8	320	161	107
600 x 900 x 11	280	140	105
900 x 900 x 12	320	160	105

Grout Shades are Approximate Guides Only,  
Actual Shade & Texture Will Depend On Job Site Condition



**MAP - EPOXY TG** is a 100 % solid epoxy grout that is stainfree, colour-fast chemical resistant for use with ceramic & Vitrified tiles, marble and stone.

**COVERAGE :**

1 kg. of **MAP - EPOXY TG** covers approximately 30 running ft. with 2mm width of joint.

**NOTE :**

It is always good practice calculating coverage to allow for 10-15 % additional material for wastage and spillage.

**SURFACE PREPARATION :**

Surface shall be sound, clean and free from dust, greece, laitance and other contaminations .

**MIXING :**

The **Base and Hardener** components shall be thoroughly mixed together using a stiff spatula or a slow speed drill with paddle attachment, until a uniform colour obtained.

**APPLICATION :**

Fill joints using float with mixed material, clean off with water and by scrubber, finish off with a clean sponge.

**Recommended For :**

- Ceramic Floor & Wall Tiles
- Quarry Tile
- Marble, Mosaic and Stone
- Vitrified Tile / Porcelain Tile

**Advantages :**

- Colour - Fast
- Weather Resistant & Crack Free
- Easy Maintenance & Non-Shrink
- Easy Application and Clean Up.

**MAP**<sup>TM</sup>